

VISCOQUICK Brabender GmbH & Co KG

Η γρήγορη και ευέλικτη μέθοδος μέτρησης του ιξώδους

When five- to ten-gram sample quantities are involved, the ViscoQuick, a compact all-purpose viscosity gage, quickly and reliably provides a basis for making decisions about the quality and usability of each raw material for any desired application. The ViscoQuick has a wide range of quality control, incoming and outgoing goods, production control and product / formulation development applications

ViscoQuick measures what?

- Ρεολογικές ιδιότητες παχύρευστων υλικών, ανάλογα με τη θερμοκρασία
- Ιδιότητες ζελατινοποίησης αμύλων και άλλων υλικών

Your benefits

Time savings

- Fast heating and cooling rates

Cost savings

- Short test times and low sample quantities (inputs of five to ten grams depending on sample type and analysis method)
- Durable measurement system

Flexibility

- Integrated cooling / heating function with flexible heating rate for a wide range of different applications
- Measuring bowl can also be used for acidic and alkaline solutions

New design

- Space-saving, simple design, easy to install

Brabender MetaBridge

- Enhanced laboratory management
- Records time, torque, temperature and viscosity readings

Technical Details

Speed 0 to 500 min⁻¹

Power connection

230 V; 50/60 Hz L + N + PE; 3 A

115 V; 50/60 Hz L + N + PE; 6 A

Dimensions (B x H x T) 430 x 350 x 640 mm

Weight ca. 36 kg netto



Brabender®